

Berger Weathercoat Tartaruga

DESCRIPTION:	A medium textured, premium quality coating based on tough, flexible acrylic co-polymer pigmented with titanium dioxide and other light fast pigments reinforced with selected mineral quartz and mica. Use of proper quality fungicides, algacides and high film build up ensures excellent weather resistance and durability.
SCOPE:	For interior and exterior. Berger Weathercoat Tartaruga provides a durable flat finish with very good properties, superb colour retention and also helps to cover hairline surface cracks and irregularities.
COMPOSITION:	Styrene Acrylic Co-polymer based, lead free.
FINISH:	Medium textured matt finish.
COLOUR:	White and as per customer's requirement.
DRYING TIME:	Touch dry – 4 hours. Hard dry – 12 to 16 hours. Over coating after 16 hours. When checked at 25°C and relative humidity below 75%. The drying time will vary depending on climatic condition at the time of application and drying.
SPECIFIC GRAVITY:	1.45 ± 0.02 Kgs/Litre
% VOLUME SOLIDS:	50 ± 2
SPREAD RATE:	1 – 2 square meter/litre. (Depending on surface conditions, type of design and roller)
THINNER / CLEAN UP:	Water. Clean the equipment immediately with water after use.
FLASH POINT:	Non-flammable
PACK SIZE:	20 Litres, 10 Litres, 5 Litres.
APPLICATION:	The application is in two stages – <ul style="list-style-type: none">• First of all select the design of your choice and the roller accordingly. Various patterned rollers are available from your local Ironmonger.• Stir well, do not thin. Apply one coat by brush to build up necessary thickness depending on type of roller selected, followed by profiled roller to obtain desire finish and allow it to dry. If the roller is of deep design, the brush coat should be of higher thickness and lower thickness for normal designed roller. The spreading rate will vary accordingly.

SURFACE PREPARATION: The surface to be coated should be clean, dry and free from all contaminants. Old. Loose flaking paint and laitance should be removed by scraping or wire brushing. Chalking surfaces should be consolidated by using Berger Stabilizing Solution

STORAGE: Store in cool, dry condition away from direct sunlight.

DISPOSAL: Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

SHELF LIFE: 1 Year, when stored in original conditions

SAFETY PRECAUTIONS Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

FIRST AID	EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
	SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
	INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BGG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt