

Murisan Plastic Emulsion

DESCRIPTION: Premium quality acrylic co-polymer based emulsion paint, pigmented with titanium dioxide and other high-grade light fast and alkali resisting pigments with excellent scrub resistance and washability. Resistant to fungus and algae. Ideal for both interior and exterior usage. Low odour.

SCOPE: Ideal for interior and exterior of masonry surfaces especially designed for Maltese limestone and Maltese conditions.
High viscosity can be thinned with water to give exceptional coverage.
High opacity matt finish, low odour.

COMPOSITION: Styrene Acrylic Emulsion Based, Lead Free

FINISH: Matt - smooth

COLOUR: Available in Brilliant White and a range of 24 attractive colours.

DRYING TIME: Surface dry - 1 hour
Re-coatable 4 hours
Checked at 25 °C and relative humidity not more than 75%.

SPECIFIC GRAVITY: 1.31 ± 0.02 Kgs/L

% VOLUME SOLIDS: 24 ± 2

SPREADING RATE: 8 –10m² / Litre, (Depending on surface conditions and absorbency).

THINNER / CLEAN UP: Water. After use clean the equipment immediately with water.

FLASH POINT Non – flammable

PACK SIZE: 18Ltrs, 10Ltrs, 5Ltrs and 2.5Ltrs

APPLICATION: Brush, roller or spray. Water can be added depending on ease of application.
Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.

SURFACE PREPARATION:

1.1 Plaster, Concrete, Cement Render, Malta Limestone and Brickwork

All surfaces must be free from dirt and grease. Freshly trowelled plaster should be allowed to dry for at least seven days.

Fungus affected areas must be treated with Murisan Anti-Moffa Solution and allowed to dry before painting.

1.2 Previously Painted Masonry Surfaces

All paint that is soft, powdered, blistered, loose or flaking should be removed by scraping, wire brushing or sanding. The surface should be clean and dry.

Gloss or semi-gloss surfaces should always be rubbed down with fine abrasive paper to provide a good key.

Limestone and other loose-bound water paints should be removed as much as possible with a dry, stiff bristle brush and sealed with a coat of Decora Super Sealer.

FINISHING:

For new work or a change in colour, apply two coats of Murisan. One coat may be applied for general maintenance painting.

STORAGE:

Store in cool, dry condition away from direct sunlight.

DISPOSAL:

Dispose as normal paint. In case of doubt, consult local authority.
Do not empty into drains, sewers or other watercourses.

SHELF LIFE:

1 Year, when stored in original conditions.

SAFETY PRECAUTIONS:

Ensure adequate ventilation in confined areas where the product is being applied.
Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

FIRST AID:

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
INHALATION	Remove into fresh air, loosen collar, and avoid excessive exertion.
INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BGG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt