

Brolac Tennis Court Dressing

DESCRIPTION: An exterior floor coating designed to slow down foot traffic. It is finely graded silica greatly improves non-skid properties for use in sports complexes, patios and pool areas. In case of tennis courts, the product gives players better floor grip to avoid skids providing safety. This elastic coating can be applied to both concrete and asphalt surfaces.

SCOPE: Ideal coating for Patio and Tennis Courts providing non-skid safe surface for play.

COMPOSITION: Styrene Acrylic Emulsion Based, Lead Free

FINISH: Fine textured

COLOUR: Cream, Green, Light Grey, Red and White.

DRYING TIME: Surface Drying - 2 hours, Overcoat Time - 4 hours, Hard Dry – 4 hours.
Checked at 25 °C and relative humidity not more than 75%.

SPECIFIC GRAVITY: 1.47 ± 0.2 Kgs / L

% VOLUME SOLIDS: 47 ± 2

SPREADING RATE: 4 m² per Litre (Depending on surface condition and absorbency).

THINNER / CLEAN UP: Water. After use clean the equipment immediately with water.

FLASH POINT: Non – flammable

PACK SIZE: 5 Litres

PRIMING: New and Previously painted asphalt and concrete surfaces
In order to provide a surface of uniform absorption, apply one coat of Berger Decora Super Sealer.

APPLICATION:

- Brush, Squeegee.
- Apply with a squeegee. Pull the squeegee along the court at a slight angle so that surplus paint flows in the direction of the surface yet to be painted.
- Any ridges should be removed at the end of each length by gently brushing with a soft house broom.
- Apply two coats, the second should be applied at right angles to the first.
- Minimum drying time of 4 hours should be allowed between coats, longer drying times may be necessary under humid conditions.
- Brolac Tennis Court Dressing is ready for use and should not normally be diluted. On very hot days, application may be eased by the addition of not more than 10% water.

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.

SURFACE PREPARATION:

1.1 New Concrete Surfaces

- Remove all dirt and loose particles thoroughly by brush / vacuum cleaner.
- Apply a coat of Berger Decora Super Sealer for uniform absorption of Tennis Court Dressing.
- Allow the surface to dry thoroughly.

1.2 Previously Painted Concrete Surfaces / New and Previously Painted Asphalt Surfaces

- Brush surface thoroughly to remove all dirt and loose particles.
- Remove any organic growth using a proprietary fungicide solution if necessary.
- Any cracks or defects in the surface should be repaired. Cut out all surface cracks and "wet" cracks by applying Brolac Tennis Court Dressing to the crack sides to avoid undue absorption of water and subsequent shrinkage of the filling. Fill cracks with exterior Crack Filler; ensuring manufacturer's instructions for use are followed. Allow filled cracks to dry thoroughly and then sandpaper to a smooth finish. Sweep surface with a soft broom to remove all dust and loose particles.

LINE MARKING:

- Allow Tennis Court Dressing to dry for 24 hours.
- Mark Court lines using Berger Line Paint, applied by brush.
- Do not apply Brolac Tennis Court Dressing during rainfall, when rain is expected or when air temperatures are expected to fall below 10°C.

STORAGE

Store in cool, dry condition away from direct sunlight.

DISPOSAL:

Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

SHELF LIFE:

1 Year, when stored in original conditions.

SAFETY PRECAUTIONS:

Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

FIRST AID:

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
INHALATION	Remove into fresh air, loosen collar, and avoid excessive exertion.
INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt