

Brolac All Purpose Primer

DESCRIPTION: Premium quality primer based on alkyd with Zinc Phosphate anticorrosive pigment. Its special formulation aids flow into the surface thus binding the fibres of the wood together to produce a smooth base. This enhances adhesion of subsequent enamel and other coatings from the Berger range.

SCOPE: The anticorrosive properties of this primer makes it popular to use on metal surfaces to protect from corrosion wherever Red oxide primer is not suitable due to its colour. Also for use on softwoods, hardwoods, hardboard.
Non-Toxic. Safe for general domestic, commercial and industrial use.

COMPOSITION: Alkyd Based, Lead Free.

FINISH: Semi Matt

COLOUR: White

DRYING TIME: Surface dry – 2 hours. Hard dry – 14 hours. Re-coatable after 14 hours. Checked at 25 °C and relative humidity not more than 75%.

SPECIFIC GRAVITY: 1.48 ± 0.02 Kgs/L

% VOLUME SOLIDS: 47 ± 2

SPREADING RATE: 10 - 12m² / Litre, (Depend on surface condition and absorbency)

THINNER / CLEAN UP: White Spirit. After use, clean equipment immediately with White Spirit.

FLASH POINT: 37° C

V.O.C. LIMIT: Cat - g(SB) – 350g/L (2010)
Product Contents: <350g/L

PACK SIZE: 2.5Lts, 1Ltr, 500Mls and 250Mls

APPLICATION: Brush, spray or roller.
Use 5% to 10% thinner for ease of application depending on the method of application.

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.

SURFACE PREPERATION: 1.1 Steel

All loose surface rust must be removed by wire brushing. Mill scale must be removed by abrasive blasting or other suitable methods using mechanical tools. Remove all other contaminants, oil, grease, etc., and ensure surface is dry before coating. Prime with one coat of Brolac All Purpose Primer.

1.2 Galvanised Iron

Remove all oil, grease and fabricators pre-treatment with a degreaser. Ensure that all surfaces are dry, then prime immediately with Brolac water thinnable Red Oxide Primer, followed by Brolac All Purpose Primer or Brolac Undercoat.

1.3 Wood

Rub down with fine abrasive and ensure that the timber is dry and free from contamination, dust off thoroughly. All knots and resinous patches should be sealed. Apply one liberal coat of Brolac All Purpose Primer.

STORAGE: Store in cool, dry condition away from direct sunlight.

DISPOSAL: Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

SHELF LIFE 2 Years, when stored in original conditions.

SAFETY PRECAUTIONS Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands. Do not breathe spray mist.

FIRST AID

EYES: In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.

SKIN: Wash skin thoroughly with soap and water or approved industrial cleaner.
DO NOT USE solvent or thinners.

INGESTION: In case of accidental ingestion, **DO NOT INDUCE VOMITING.** Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 3000 MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996 FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt