

## Brolac Red Oxide Primer

<b>DESCRIPTION:</b>	An economical Red oxide Primer developed to take care of the corrosion of ferrous substrate. Based on synthetic alkyd resin and anticorrosive red oxide pigment which protect the metal from atmospheric corrosion due to salty humid condition. Premium quality primer based on alkyd with Zinc Phosphate anticorrosive pigment. Its special formulation aids flow into the surface thus binding the fibres of the wood together to produce a smooth base. This enhances adhesion of subsequent enamel and other coatings from the Berger range.
<b>SCOPE:</b>	An economical red oxide primer for metallic substrate to protect the surface from corrosion, such as mild steel, window grills, balconies grills, compound fencing etc. Non-Toxic. Safe for general domestic, commercial and industrial use.
<b>COMPOSITION:</b>	Alkyd Based, Lead Free.
<b>FINISH:</b>	Semi Matt
<b>COLOUR:</b>	Red oxide
<b>DRYING TIME:</b>	Surface dry – 2 hours. Hard dry – 12 hours. Re-coatable after 12 hours. Checked at 25 °C and relative humidity not more than 75%.
<b>SPECIFIC GRAVITY:</b>	1.31 ± 0.02 Kgs/L
<b>% VOLUME SOLIDS:</b>	49 ± 2
<b>SPREADING RATE:</b>	10 - 12m <sup>2</sup> / Litre. (Depend on surface condition and absorbency)
<b>THINNER / CLEAN UP:</b>	White Spirit. After use, clean equipment immediately with White Spirit.
<b>FLASH POINT:</b>	37° C
<b>PACK SIZE:</b>	20 Litres, 5 Litres, 2.5 Litres, 1 Litre, 500ml and 250ml.
<b>APPLICATION:</b>	Brush, spray or roller. Use 5% to 10% thinner for ease of application depending on the method of application. Do not overcoat with epoxy or chlorinated rubber products Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surface temperature is 3°C or more above dew point.

**SURFACE PREPERATION:** All loose surface rust must be removed by wire brushing. Mill scale must be removed by abrasive blasting or other suitable methods using mechanical tools. Remove all other contaminants, oil, grease, by wiping with white spirit or degreaser. Ensure surface is dry before coating. Previously painted and rusted surfaces should be clean with abrasive paper, wiping off dust followed by one coat of Brolac Red Oxide Primer.

---

**STORAGE:** Store in cool, dry condition away from direct sunlight.

---

**DISPOSAL:** Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses

---

**SHELF LIFE** 2 Years, when stored in original conditions.

---

**SAFETY PRECAUTIONS** Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands. Do not breathe spray mist.

---

<b>FIRST AID</b>	<b>EYES</b>	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
	<b>SKIN</b>	Wash skin thoroughly with soap and water or approved industrial cleaner. <b>DO NOT USE</b> solvent or thinners.
	<b>INGESTION</b>	In case of accidental ingestion, <b>DO NOT INDUCE VOMITING.</b> Obtain immediate medical attention.

---

**DISCLAIMER:**

*The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.*



Manufactured by BERGER PAINTS (MALTA) LTD.  
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06  
MALTA - EUROPE  
TEL: +356 2165 8855 / +356 2165 2996  
FAX: +356 2165 9409  
EMAIL: [info@berger.com.mt](mailto:info@berger.com.mt)  
WEBSITE: [www.berger.com.mt](http://www.berger.com.mt)