

## Berger Gypsum Primer

<b>DESCRIPTION:</b>	Premium quality acrylic co-polymer based primer with good alkali resisting properties designed to provide a sound base for coatings from the Berger range. Highly recommended for other interior smooth coatings also.
<b>SCOPE:</b>	As a primer prior to application of finish coat, that provides good anchorage for subsequent coats and also improves the coverage of finish coats. For Interior concrete, plaster, masonry, brickwork, blockwork and gypsum.
<b>COMPOSITION:</b>	Styrene Acrylic Emulsion based, lead free
<b>FINISH:</b>	Smooth matt
<b>COLOUR:</b>	White
<b>DRYING TIME:</b>	Dries within 2 hours. Re-coatable after 4 hours. Checked at 25 °C and relative humidity not more than 75%.
<b>SPECIFIC GRAVITY:</b>	1.48 ± 0.02 Kgs/L
<b>% VOLUME SOLIDS:</b>	28 ± 2
<b>SPREADING RATE:</b>	8 – 10 square meter/litre (Depending on surface condition and absorbency)
<b>THINNER / CLEANER:</b>	Water. After use clean the equipment immediately with water.
<b>FLASH POINT:</b>	Non-flammable.
<b>PACK SIZE:</b>	5 Litres & 10 Litres
<b>APPLICATION:</b>	Brush, Roller, Spray.  Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.
<b>SURFACE PREPARATION:</b>	The performance of this coating is directly related to the degree of surface preparation. Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from laitance. Remove laitance by wire brush or sweep blast.

If surface is previously painted, ensure that all peeling or flaking paint is removed completely. Thoroughly dust down the entire surface.  
Fungus affected areas must be treated with Murisan Anti-Moffa Solution and allowed to dry before painting.

---

**STORAGE:** Store in cool, dry condition away from direct sunlight.

---

**DISPOSAL:** Dispose as normal paint. In case of doubt, consult local authority.  
Do not empty into drains, sewers or other watercourses.

---

**SHELF LIFE:** 1 Year, when stored in original conditions.

---

**SAFETY PRECAUTIONS:** Ensure adequate ventilation in confined areas where the product is being applied.  
Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

---

**FIRST AID:**

<b>EYES</b>	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
<b>SKIN</b>	Wash skin thoroughly with soap and water or approved industrial cleaner. <b>DO NOT USE</b> solvent or thinners.
<b>INHALATION</b>	Remove into fresh air, loosen collar, and avoid excessive exertion.
<b>INGESTION</b>	In case of accidental ingestion, <b>DO NOT INDUCE VOMITING</b> . Obtain immediate medical attention.

---

**DISCLAIMER:**

*The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.*



Manufactured by BERGER PAINTS (MALTA) LTD.  
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06  
MALTA - EUROPE  
TEL: +356 2165 8855 / +356 2165 2996  
FAX: +356 2165 9409  
EMAIL: [info@berger.com.mt](mailto:info@berger.com.mt)  
WEBSITE: [www.berger.com.mt](http://www.berger.com.mt)