

## Rust Master

<b>DESCRIPTION:</b>	Berger Rust Master is a product specially developed to remove the rust from corroded surfaces.
<b>SCOPE:</b>	Converts rust to a sound surface in a few minutes. Ready for use, simply to apply.
<b>COMPOSITION:</b>	A solution of acids.
<b>SPECIFIC GRAVITY:</b>	1.33 ± 0.02 Kgs/L
<b>SPREADING RATE:</b>	Entirely depends on the severity of corrosion.
<b>THINNER / CLEAN UP:</b>	Wash brushes and equipment in clean water immediately after use.
<b>FLASH POINT:</b>	Water based product.
<b>PACK SIZE:</b>	250 ml, 500 ml, 1 L, 2 L and 5 L
<b>APPLICATION:</b>	<ul style="list-style-type: none"><li>• Shake well and pour the quantity to be used in a <b>plastic container, do not use metal can.</b></li><li>• Apply by brush onto the rusty area well into any pitted areas and edges. Do not apply on painted areas as this may stain the paint.</li><li>• Rust Master will change the colour of the rust to a lighter shade while reacting with rust.</li><li>• Allow Rust Master to react with rust till there is no further change in colour. This process will depend on harshness of rust. Re apply in case of severe rust cases.</li><li>• Wash thoroughly with water, wipe with a clean cloth and allow to dry.</li><li>• Immediately after drying, apply a rust protective Primer / Undercoat e.g. Brolac Red Oxide Primer, Brolac All Purpose Primer or Brolac Undercoat and subsequently the topcoat.</li><li>• Most solvent-based products are suitable to overcoat. If in doubt, test a small area first. Treated surfaces should be coated as soon as possible.</li><li>• Do not pour any surplus Rust Master back into the original container after use.</li></ul>
<b>SURFACE PREPARATION:</b>	Ensure surface is clean and free from loose rust, oil and grease.
<b>STORAGE:</b>	Protect from frost and direct sunlight.
<b>DISPOSAL:</b>	Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

**SHELF LIFE:** 2 Years, when stored in original conditions.

---

**SAFETY PRECAUTIONS** Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

---

<b>FIRST AID</b>	<b>EYES</b>	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
	<b>SKIN</b>	Wash skin thoroughly with soap and water or approved industrial cleaner. <b>DO NOT USE</b> solvent or thinners.
	<b>INGESTION</b>	In case of accidental ingestion, <b>DO NOT INDUCE VOMITING.</b> Obtain immediate medical attention.

---

**DISCLAIMER:**

*The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.*



Manufactured by BERGER PAINTS (MALTA) LTD.  
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06  
MALTA - EUROPE  
TEL: +356 2165 8855 / +356 2165 2996  
FAX: +356 2165 9409  
EMAIL: [info@berger.com.mt](mailto:info@berger.com.mt)  
WEBSITE: [www.berger.com.mt](http://www.berger.com.mt)