

Terrace Water Barrier

DESCRIPTION: Terrace Water Barrier is an alkali resisting clear coat based on styrene-acrylic co-polymer formulated to penetrate into porous surfaces and seals concrete, semi glossy and matt tiles without yellowing and with excellent adhesion. It retains the same tile colour and gives good washable finish. Easy to clean. Low odour.

SCOPE: Designed as a water-proofer for Balcony / Terrace tiles.
Protects Balcony / Terrace and covers fine cracks.
Provides a water resistant, flexible, long life decorative finish, reducing maintenance and costs.

COMPOSITION: Styrene Acrylic Emulsion Based, Lead Free

FINISH: Smooth, Clear, Semi Gloss

COLOUR: Clear

DRYING TIME: Dry within 2 hours. Re-coatable after 24 hours
Checked at 25 °C and relative humidity not more than 75%.

SPECIFIC GRAVITY: 1.02 ± 0.01 Kgs/L

% VOLUME SOLIDS: 45 ± 2

SPREADING RATE: 4 - 6m² / Litre (Depending on surface condition and its absorbency).

THINNER / CLEAN UP: Water. After use clean the equipment immediately with water.

FLASH POINT: Non - flammable

PACK SIZE: 2.5 Litres

APPLICATION: Brush, roller, Spray. Ready to use – do not thin.
Apply 2 coats – allowing 24 hours before applying the second coat.

Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply when surface temperature is 3°C or more above dew point.

SURFACE PREPARATION: Balcony / Terrace should be swept clean of loose dirt, gravel or loose particles. Fungus affected areas must be treated with Murisan Anti Moffa solution and allowed to dry before painting. It is advisable to apply one coat of Berger Stabilising Solution for cement based concrete floor.

NOTES: Appearance of this product in the container is milky white, which transforms to clear on drying.

STORAGE: Store in cool, dry condition away from direct sunlight.

DISPOSAL: Dispose as normal paint. In case of doubt, consult local authority.
Do not empty into drains, sewers or other watercourses.

SHELF LIFE: 1 Year, when stored in original conditions.

SAFETY PRECAUTIONS: Ensure adequate ventilation in confined areas where the product is being applied.
Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

FIRST AID:

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
INHALATION	Remove into fresh air, loosen collar, and avoid excessive exertion.
INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING . Obtain immediate medical attention.

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt