

## Tex Primer

**SCOPE:** A premium quality acrylic co-polymer primer with good alkali resisting properties designed to provide a sound base for coatings from the Berger range. It is also highly recommended for other exterior smooth coatings.

**USE:** **Area of Use** – Interior & Exterior  
**Substrate** – Concrete, plaster, masonry, brickwork, blockwork

**FINISH:** Smooth matt

**COLOUR:** White

Substrate temperature	Dry to touch	Overcoating interval	
		Minimum	Maximum
25°C	3 hours	16 hours	Indefinite
35°C	2 hours		
45°C	1 hour		

**VOLUME SOLIDS:** 2.8 ± 2

**SPECIFIC GRAVITY:** 1.07 ± 0.02

	Recommended dry film thickness per coat		Spread Rate
	Minimum	25 microns	11.2m <sup>2</sup> per Litre
Maximum	35 microns	8m <sup>2</sup> per Litre	
Typical	30 microns	9.33m <sup>2</sup> per Litre	

**FLASH POINT:** N/A

**THINNER / CLEANER:** Sweet water

**SHELF LIFE:** 1 Year

**STORAGE:** Store in cool, dry condition

**DISPOSAL:** Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

**SURFACE PREPARATION:** The performance of this coating is directly related to the degree of surface preparation. Ensure surface is clean, dry and free from all contaminants. Surface must be sound and free from

laitance. Remove laitance by wire brush or sweep blast.  
If surface is previously painted, ensure that all peeling or flaking paint is removed completely.  
Thoroughly dust down the entire surface.

---

**APPLICATION METHOD:** Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surfaced temperature is 3°C or more above dew point.  
**BRUSH** – Recommended  
**ROLLER** – May also be used

---

**SAFETY PRECAUTIONS:** Avoid contact with the skin and eyes. Wear suitable protective clothing such as overalls, goggles, dust mask and gloves. Use a barrier cream.  
Ensure that there is adequate ventilation in confined areas where the product is being applied.

---

**FIRST AID:**

<b>EYES</b>	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
<b>SKIN</b>	Wash skin thoroughly with soap and water or approved industrial cleaner. <b>DO NOT USE</b> solvent or thinners.
<b>INHALATION</b>	Remove into fresh air, loosen collar, and avoid excessive exertion.
<b>INGESTION</b>	In case of accidental ingestion, <b>DO NOT INDUCE VOMITING</b> . Obtain immediate medical attention.

---

**V.O.C. Limit:** Cat-(c) WB – 40g/L (2010)  
Product Contents: <40g/L

---

**BERGER is a Trade Mark of Asian Paints International Private Limited**

**DISCLAIMER:**

*The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.*



Manufactured by BERGER PAINTS (MALTA) LTD.  
HF66, INDUSTRIAL ESTATE, HAL FAR BBG 06 – MALTA  
TEL: +356 2165 8855 / +356 2165 2996  
FAX: +356 2165 9409  
EMAIL: [info@berger.com.mt](mailto:info@berger.com.mt)  
WEBSITE: [www.berger.com.mt](http://www.berger.com.mt)