

Brolac Weathercoat No.2

DESCRIPTION:	Premium quality smooth coating based on a tough, flexible acrylic-copolymer, pigmented with titanium dioxide and other high grade light fast alkali resisting pigments, and reinforced with selected mineral quartz and mica. Special formulation with fungicides and algacides. Its build-up ensures outstanding weather resistance and durability, which helps to cover hairline surface cracks and irregularities. Ideal as a decorative and protective coating.
SCOPE:	Long life, highly attractive external smooth finish for Maltese Limestone, Plaster, Concrete Block, etc. May also be used internally.
COMPOSITION:	Styrene Acrylic Emulsion Based, Lead Free.
FINISH:	Smooth with slight sheen
COLOUR RANGE:	Available in Brilliant White, Magnolia, Light Stone.
DRYING TIME:	Touch dry - 1 hour Re-coat after 4 hours
SPECIFIC GRAVITY:	1.31 ± 0.02 Kgs./L
% VOLUME SOLIDS:	36 ± 2
SPREADING RATE:	6 – 8 m ² / Litre (Depending on surface condition and absorbency).
THINNER / CLEAN UPS:	Water. After use clean the equipment immediately with water.
FLASH POINT:	Non - flammable
PACK SIZES:	10 Litres, 5 Litres, 3 Litres
APPLICATION:	Brush, Roller or conventional spray. Can be diluted with water for ease of application only. Ensure adequate ventilation during application and drying. Do not apply when humidity exceeds 95% and condensation is likely. Only apply coating when surfaced temperature is 3°C or more above dew point.

SURFACE PREPARATION: Prepare surfaces as follows:

SURFACE CONDITION	PREPARATION
All Surfaces	Ensure surfaces are sound, clean and free from dust and grease.
Mould, algae, or other organic growth.	Apply Berger Murisan Anti Moffa Solution. Refer data sheet.
Greasy, dirty	Wash well with mild detergent solution. Rinse thoroughly with clean water and allow drying.
Loose and flaking surfaces	Remove poorly adhering paint and prime with Brolac Dualcote.
Chalky, friable or porous surfaces	Prime with Brolac Stabilising Solution
Surfaces painted with gloss paint	Wash thoroughly and rub down with waterproof abrasive paper. Rinse thoroughly with clean water and allow drying.

STORAGE: Store in cool, dry condition away from direct sunlight.

DISPOSAL: Dispose as normal paint. In case of doubt, consult local authority. Do not empty into drains, sewers or other watercourses.

SHELF LIFE: 1 Year, when stored in original conditions.

SAFETY PRECAUTIONS: Ensure adequate ventilation in confined areas where the product is being applied. Avoid contact with skin and eyes. Wear suitable protective equipments such as overalls, goggles, dust mask and gloves. Use barrier cream for hands.

FIRST AID:

EYES	In the event of accidental splashes, flush eyes with warm water immediately and obtain medical advice.
SKIN	Wash skin thoroughly with soap and water or approved industrial cleaner. DO NOT USE solvent or thinners.
INHALATION	Remove into fresh air, loosen collar, and avoid excessive exertion.
INGESTION	In case of accidental ingestion, DO NOT INDUCE VOMITING. Obtain immediate medical attention.

DISCLAIMER:

The information provided on this data sheet is not intended to be complete and is provided as general advice only. It is the responsibility of the user to ensure that the product is suitable for the purpose for which he wishes to use it. As we have no control over the treatment of the product, the standard of surface preparation of the substrate, or other factors affecting the use of this product, we are not responsible for its performance nor would we accept any liability whatsoever or howsoever arising from the use of this product unless specifically agreed to in writing by us. The information contained in this data sheet may be modified by us from time to time, and without notice, in the light of our experience and continuous product development.



Manufactured by BERGER PAINTS (MALTA) LTD.
HF66, INDUSTRIAL ESTATE, HAL FAR BGG 06
MALTA - EUROPE
TEL: +356 2165 8855 / +356 2165 2996
FAX: +356 2165 9409
EMAIL: info@berger.com.mt
WEBSITE: www.berger.com.mt